

CO223M - Lincat Convector Manual+ Electric Counter-top Convection Oven - W 810 mm - D 850 mm - 3.0 kW Able to roast, braise, bake and reheat, a CO223M Convector convection oven is a powerful addition to any commercial kitchen.

- 2 x GN1/1 capacity
- Easy-to-use knob-driven control, and electronic fan control
- Mechanical temperature control from 60° to 260° C
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan
- Two fan speeds standard for general use and slow for delicate items
- 120 minute count down timer with electronicallycontrolled buzzer
- Oven lamps flash when cook cycle has finished see when your food is done even in the busiest

Specifications

| Specifications | | | | | |
|----------------------|-----------------------------------|-----------------------|-----------------|--|--|
| Summary | | Power and Performance | | | |
| Brand | Lincat | Total Power kW | 3.0 | | |
| Range | Convector | Temperature Range °C | 60-260 | | |
| Series | Manual+ | IP Rating | IP23 | | |
| Power Type | Electric | Controls Position | Right hand side | | |
| Unit Type | Counter-top | Temperature Control | Mechanical | | |
| Available in UK Only | No | Timer Range mins | 1-120 | | |
| UK Warranty | 2 Years Parts and Labour Warranty | Oven Rating kW | 2.8 | | |
| Export Warranty | Contact your local dealer | | | | |
| GTIN | 5056105118268 | | | | |

Key Specifications Capacity Stackable **Gastronorm Capacity** 2 x GN1/1 Yes (with optional kit) Feet Height/Type **Euronorm Capacity** 2 x 600 mm x 400 mm 55mm/adjustable Continuous Plug-In Door Seal Shelf Spacing mm Removable Inner Door Glass Yes **Sheet Pan Capacity** 2 x 660 mm x 460 mm **Handle Type Capacity Litres** Grab Vented Door Yes Reversible Door Nο Door Type Drop down **Phased Cooking** No Shelf Timer(s) (Number) No Grill Element/Mode No **Core Temp Probe** No Steam Injection No Fan(s) Speed 2 Fan(s) Type Bi-Directional Number of Fan(s) **Euronorm Compatible** Yes **Sheet Pan Compatible** Removeable Shelf Guides Yes **Manual Mode** Yes Programmable No Timer Type Mechanical Number of Shelves included 2 **Number of Shelf Positions** 2 Type of Lighting Halogen Bulb Construction/Finish 430 S/S cavity **GN** Compatible Yes

| Weights and Dimensions | | Supply Connections | |
|---------------------------|------|---------------------------------------|-------|
| Unit Height (External) mm | 645 | Requires Installation | No |
| Unit Width (External) mm | 810 | Requires Electrical Supply | Yes |
| Unit Depth (External) mm | 850 | UK 3 Pin Plug | Yes |
| Height (Internal) mm | 308 | Requires Hardwiring | No |
| Width (Internal) mm | 690 | Electrical Supply Rating Watts | 3,000 |
| Depth (Internal) mm | 470 | Single Phase Amps | 13.0 |
| Shelf Dimensions Width mm | 660 | Single Phase Voltage | 230 |
| Shelf Dimensions Depth mm | 425 | USB Port | No |
| Net Weight Kg | 78.9 | | |

 Packed Weight Kg
 91

 Packed Height cm
 81.5

 Packed Width cm
 88

 Packed Depth cm
 100


Available Accessories


CO200/FS Lincat Convector Floor Stand for CO223M/CO235M/CO235T Convection Ovens - with 4 Runners - W 810 mm


CO200/LFSK Lincat Convector Low Floor Stand and Stacking Kit for C0223M/C0223T/C0235M/C0235T Convection Ovens - with 1 Runner - W

810 mm

Technical Picture









Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm