Export Warranty

GTIN



CO235M - Lincat
Convector Manual+
Electric Counter-top
Convection Oven - W 810
mm - D 850 mm - 4.8 kW

Able to roast, braise, bake and reheat, a CO235M Convector convection oven is a powerful addition to any commercial kitchen.

3 x GN1/1 capacity

Contact your local dealer

5056105118282

- Easy-to-use knob-driven control, and electronic fan control
- Mechanical temperature control from 60° to 260° C
- Even heat distribution thanks to electronically controlled two-speed, bi-directional fan
- Two fan speeds standard for general use and slow for delicate items
- 120 minute count down timer with electronicallycontrolled buzzer
- Oven lamps flash when cook cycle has finished see when your food is done even in the busiest kitchen

Specifications Summary Power and Performance Brand Lincat Total Power kW 4.8 Range Convector Temperature Range °C 60-260 Series IP Rating IP23 Manual+ **Power Type Controls Position** Electric Right hand side Temperature Control **Unit Type** Counter-top Mechanical Available in UK Only Timer Range mins 1-120 **UK Warranty** Oven Rating kW 2 Years Parts and Labour Warranty 4.6

Key Specifications Capacity Stackable **Gastronorm Capacity** 3 x GN1/1 Yes (with optional kit) **Euronorm Capacity** Feet Height/Type 3 x 600 mm x 400 mm 55mm/adjustable Continuous Plug-In Door Seal Shelf Spacing mm **Removable Inner Door Glass** Yes **Sheet Pan Capacity** 3 x 660 mm x 460 mm **Handle Type Capacity Litres** 96.0 Grab Vented Door Yes Reversible Door Νn Door Type Drop down **Phased Cooking** No Shelf Timer(s) (Number) No Grill Element/Mode No **Core Temp Probe** No Steam Injection No Fan(s) Speed 2 Fan(s) Type Bi-Directional Number of Fan(s) **Euronorm Compatible** Yes **Sheet Pan Compatible** Removeable Shelf Guides Yes **Manual Mode** Yes Programmable No Timer Type Mechanical Number of Shelves included 3 **Number of Shelf Positions** 3 Type of Lighting Halogen Bulb Construction/Finish 430 S/S cavity **GN** Compatible Yes Woights and Dimo

weights and Dimensions		Supply Connections	Supply Connections	
Unit Height (External) mm	645	Requires Installation	Yes	
Unit Width (External) mm	810	Requires Electrical Supply	Yes	
Unit Depth (External) mm	850	UK 3 Pin Plug	No	
Height (Internal) mm	308	Requires Hardwiring	Yes	
Width (Internal) mm	690	Electrical Supply Rating Watts	4,800	
Depth (Internal) mm	470	Single Phase Amps	20.5	
Shelf Dimensions Width mm	660	Single Phase Voltage	230	
Shelf Dimensions Depth mm	425	Three Phase Amps	L1=6.9; L2=6.9; L3=6.9	
Net Weight Kg	80.6	Three Phase Voltage	400	
		USB Port	No	

Shipping

 Packed Weight Kg
 92.7

 Packed Height cm
 81.5

 Packed Width cm
 88

 Packed Depth cm
 100

Available Accessories


CO200/FS Lincat Convector Floor Stand for C0223M/C0223T/C0235M/C0235T Convection Ovens - with 4 Runners - W 810 mm


CO200/LFSK Lincat Convector Low Floor Stand and Stacking Kit for C0223M/C0223T/C0235M/C0235T Convection Ovens - with 1 Runner - W


810 mm

Technical Picture

Product Code: C0235M Page Number: 2 Print Date: 20/01/2021









Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm