SILVERLINK 600



ECG6 - Lincat Silverlink 600 Electric Counter-top Chargrill - W 600 mm -8.0 kW

Create that distinctive chargrilled flavour and branded appearance without the need for messy lava rocks with the Silverlink 600 Electric Chargrill.

- Offers the authentic taste and branded appearance of chargrilled food without the need for lava rock
- High heat retention of cast iron grids means there is no waiting for the grill to recover to cooking temperature
- The water bath keeps food succulent and reduces shrinkage, while the high heat retention cast iron grids ensure your output stays high throughout operation
- Hinging interlocked elements and integral water bath makes cleaning easier
- Integral splashguard with water funnel enables refilling of tank without cooling the cooking grid
- High temperature safety cut out for protection if water bath runs dry

| Summary | | Power and Performance | |
|----------------------|-----------------------------------|---------------------------------|------------|
| Brand | Lincat | Total Power kW | 8.0 |
| Range | Silverlink 600 | IP Rating | IP23 |
| Power Type | Electric | Cooking Area (Width x Depth) mm | 470 x 400 |
| Unit Type | Counter-top | Temperature Control | Mechanical |
| Available in UK Only | No | | |
| UK Warranty | 2 Years Parts and Labour Warranty | | |
| Export Warranty | Contact your local dealer | | |
| GTIN | 5056105104698 | | |

| key Specifications | | Сараспу | |
|---------------------------|------|---------------------------------------|---|
| Number of Heat Zones | 1 | Product Output per Hour | 70 x 225g [8oz] steaks [chilled], 90 x 115g [4oz] |
| Weights and Dimensions | | Supply Connections | |
| Unit Height (External) mm | 385 | Requires Installation | Yes |
| Unit Width (External) mm | 600 | Requires Electrical Supply | Yes |
| Unit Depth (External) mm | 620 | UK 3 Pin Plug | No |
| Net Weight Kg | 29.8 | Requires Hardwiring | Yes |
| | | Electrical Supply Rating Watts | 8,000 |
| | | Single Phase Amps | 34.8 |
| | | Single Phase Voltage | 230 |
| | | Three Phase Amps | L1=11.6; L2=11.6; L3=11.6 |
| | | Three Phase Voltage | 400 |

Shipping

| Packed Weight Kg | 32.78 |
|------------------|-------|
| Packed Height cm | 59.5 |
| Packed Width cm | 70 |
| Packed Depth cm | 70 |

Available Accessories

CC6 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal with Doors - W 600 mm

CN₆ Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 600 mm




Available Accessories


HC6 Lincat Silverlink 600 Free-standing Heated Open-Top Pedestal with Doors - W 600 mm - 0.5 kW


HCL6 Lincat Silverlink 600 Free-standing Heated Pedestal with Legs and Doors - W 600 mm - 0.5 kW

SLS6 Lincat Silverlink 600 Free-standing Floor Stand - for units W 600 mm

Technical Picture













Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm



Product Code: ECG6 Page Number: 3 Print Date: 06/03/2023