



LCSH106I - Lincat CombiSlim 1.06 Electric Counter-top Combi Oven with Hoodini - Injection - W 513 mm - 8.4 + 2.2 kW

Choose CombiSlim with a Ventless Hoodini solution, to gain maximum flexibility using minimum space.

- ✓ Ideal for where venting to the atmosphere is impractical, allow the setup of a cooking station in previously unsuitable areas of a building
- ✓ Utilise non-traditional spaces in the kitchen, front of house or back bar to diversify operations
- ✓ Gain maximum flexibility using minimum space with CombiSlim ovens. These combi ovens measure only 51.4 cm in width and fit into all professional kitchens
- ✓ CombiSlim ovens are ideal for small-scale food production in take-away shops, cafés, etc
- ✓ Intuitive touch display SmartTouch® for programming
- ✓ 1/1GN compatible
- ✓ Steam injection, with CombiSmart® humidity control
- ✓ Ability to create cooking programmes with up to 15 steps
- ✓ Rack timer allowing accurate cooking times for different items on different shelves
- ✓ Two-step safety handle

Specifications

Summary		Power and Performance	
Brand	Lincat	Total Power kW	8.4 + 2.2
Range	Lincat Combi Ovens	Temperature Range °C	30-300
Series	CombiSlim	IP Rating	IPX5
Power Type	Electric	Temperature Control	Electronic
Unit Type	Counter-top	Oven Rating kW	Steam connection = N/A; Hot air connection = 8.4
Available in UK Only	Yes		
UK Warranty	2 Years Parts and Labour Warranty		
GTIN	5056105121763		

Key Specifications		Capacity	
WRAS Approved	Yes	Gastronorm Capacity	6 x GN1/1 (20mm deep)
Type of Lighting	Halogen	Portions per Day	60
Number of Grids included	0		

Weights and Dimensions		Supply Connections	
Unit Height (External) mm	1174	Requires Installation	Yes
Unit Width (External) mm	514	Requires Electrical Supply	Yes
Unit Depth (External) mm	962	UK 3 Pin Plug	Yes
Height (Internal) mm	350	Requires Hardwiring	Yes
Width (Internal) mm	400	Electrical Supply Rating Watts	8,400 + 2,200
Depth (Internal) mm	630	Single Phase Amps	9
Net Weight Kg	100	Single Phase Voltage	230
		Three Phase Amps	L1=14.0; L2=14.0; L3=14.0
		Three Phase Voltage	400
		Water Connection Pressure Bar	2.5-6
		Drain Connection	DN 40 mm
		Water Connection	3/4"

Shipping

Packed Weight Kg	110
Packed Height cm	123.8
Packed Width cm	80
Packed Depth cm	120

Available Accessories

LCA3003	Lincat Combi Oven Imperial Non-stick Container - GN1/1(325 x 530 mm) - 20 mm deep
LCA3005	Lincat Combi Oven Imperial Non-stick Container - GN1/1(325 x 530 mm) - 40 mm deep
LCA3007	Lincat Combi Oven Imperial Non-stick Container - GN1/1(325 x 530 mm) - 60 mm deep
LCA3009	Lincat Combi Oven Imperial Pizza and Grilling Sheet - GN1/1(325 x 530 mm)
LCA3011	Lincat Combi Oven Imperial Grilling Grid - GN1/1(325 x 530 mm)
LCA3012	Lincat Combi Oven Imperial Potato Grid - GN1/1(325 x 530 mm) - 28 Potato Capacity
LCA3013	Lincat Combi Oven Imperial Multi-tray - 8 Moulds - GN1/1(325 x 530 mm)
LCA3015	Lincat Combi Oven Non-stick Aluminium Baking Sheet - GN1/1(325 x 530 mm)
LCA3017	Lincat Combi Oven Non-stick Perforated Aluminium Baking Sheet - GN1/1(325 x 530 mm)
LCA3019	Lincat Combi Oven Silicone Baking Mat - GN1/1(325 x 530 mm)
LCA3021	Lincat Combi Oven Steamfry Basket - GN1/1(325 x 530 mm)
LCA3023	Lincat Combi Oven Rack for Spare Ribs - GN1/1(325 x 530 mm)
LCA3024	Lincat Combi Oven Chicken Grid - GN1/2(325 x 265 mm) - 4 Chicken Capacity
LCA3025	Lincat Combi Oven Chicken Grid - GN1/1(325 x 530 mm) - 8 Chicken Capacity
LCA4001	Lincat Combi Oven Software Key - Quick Select Recipes (QSR)
LCA6006	Lincat Combi Oven Static Stand for CombiSlim - Open Stand
LCA6007	Support Rail Cassette for LCA6006 Stand for CombiSlim - 10 Support Rails
LCC1001	Hydro Shield 3600 (L) Water Filter Cartridge - Recommended for CombiSlim and Visual Cooking 1.06/1.10
LCC1002	Hydro Shield 6000 (XL) Water Filter Cartridge - Recommended for Visual Cooking 1.20/2.06/2.10/2.20 and all Combi Ovens in hard water areas
LCC1003	Hydro Shield 3600 (L) Water Filter Kit - Including Filter, Filter Head and Hose - Recommended for CombiSlim and Visual Cooking 1.06/1.10
LCC1004	Hydro Shield 6000 (XL) Water Filter Kit - Including Filter, Filter Head and Hose - Recommended for 1.20/2.06/2.10/2.20 + all Ovens in hard water areas
LCC2003	Lincat Protect Intense Detergent - 2 x 5l
LCC2005	Lincat Protect Cleaning Package - 6 x 5l Intense Detergent and 2 x 5l Rinse Aid
LCC2006	Lincat Protect Rinse Aid - 2 x 5l
OCG6111	1/1 GN GRID-S/STEEL - P/NO. GN1/1-ID6 2003



Lincat Limited

Whisby Road,
Lincoln, LN6 3QZ,
United Kingdom

Company No: 2175448

A member company of



Customer Care

Tel: +44 1522 875500
Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536
Email: export@lincat.co.uk

Opening Hours

Monday – Friday:
8.30am – 5pm