



## J5/N - Lincat Silverlink 600 Natural Gas Free-standing Single Tank Fryer - 1 Basket - W 300 mm - 12.0 kW

Deliver perfectly crisp on the outside and fluffy on the inside chips time after time with the Silverlink 600 Free Standing Gas Fryer.

- ✓ Single tank fryer delivering 22.5kg of chips an hour, perfect for pubs, restaurants and care homes
- ✓ Piezo ignition for easy lighting
- ✓ Front mounted controls for safety
- ✓ Heavy duty nickel plated baskets for the most demanding of operations
- ✓ Thermostatically controlled to give accurate cooking temperatures throughout cooking. Flame failure device and top temperature cut out ensures safe operation.
- ✓ Internal drain off tap for easy removal of cooking oil
- ✓ Cool zone collects cooking debris - gives cleaner cooking results and saves money by prolonging the life of the oil

### Specifications

Summary		Power and Performance	
<b>Brand</b>	Lincat	<b>BTU per Hour</b>	40,944
<b>Range</b>	Silverlink 600	<b>Total Power kW</b>	12.0
<b>Power Type</b>	Gas	<b>Temperature Range °C</b>	110-190
<b>Gas Type</b>	Natural Gas	<b>Temperature Control</b>	Mechanical
<b>Unit Type</b>	Free-standing		
<b>Available in UK Only</b>	No		
<b>UK Warranty</b>	2 Years Parts and Labour Warranty		
<b>Export Warranty</b>	Contact your local dealer		
<b>GTIN</b>	5056105105121		

Key Specifications		Capacity	
<b>Number of Baskets</b>	1	<b>Product Output per Hour</b>	18kg chips -12mm [frozen], 22.5kg chips - 12mm [ch]
<b>Number of Tanks</b>	1	<b>Capacity Litres</b>	12.0
<b>Gravity Filtration</b>	No		
<b>Pumped Filtration</b>	No		
<b>Drain Location</b>	Internal		

Weights and Dimensions		Supply Connections	
<b>Unit Height (External) mm</b>	1060	<b>Requires Installation</b>	Yes
<b>Unit Width (External) mm</b>	300	<b>Requires Electrical Supply</b>	No
<b>Unit Depth (External) mm</b>	690	<b>Gas Connection BSP</b>	1/2"
<b>Net Weight Kg</b>	43	<b>Gas Consumption at full rate Natural m³ per Hour</b>	1.14
		<b>Gas Pressure Natural mbar</b>	16.3
		<b>Total heat input at full rate Natural kW</b>	11.5
		<b>Total heat input at full rate Natural BTU per hour</b>	38,900




## Shipping

Packed Weight Kg	47.3
Packed Height cm	122
Packed Width cm	85
Packed Depth cm	45

## Available Accessories

<b>CH01</b>	Caterflex Hose 1/2" - 1 Metre - for use with units up to 66,000 BTU
<b>CH02</b>	Caterflex Hose 1/2" - 1.5 Metre - for use with units up to 56,000 BTU

## Technical Picture





**Lincat Limited**

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

**Company No:** 2175448

A member company of



**Customer Care**

**Tel:** +44 1522 875500  
**Email:** care@lincat.co.uk

**Export Customers**

**Tel:** +44 1522 875536  
**Email:** export@lincat.co.uk

**Opening Hours**

**Monday – Friday:**  
8.30am – 5pm