



## DYNAMIC PREPARATION

**TECHNICAL SPECIFICATIONS** 

External dimensions (WxDxH)

·Width: 280 mm

·Depth: 512 mm

·Height: 735 mm Net weight: 4 Kg

Hourly production: 100 Kg - 150 Kg

P/N 1020060

HAND OPERATED POTATO CHIPPING MACHINE



## Hand chipping machine CF-5 · 8 x 8 mm (5/16" x 5/16")

IDEAL TO MAKE PERFECT FRENCH FRIES FOR RESTAURANTS AND LARGE KITCHENS.

Output: 100 - 150 Kg./h.

Equipped with a knife block and pusher set.

- · Light stainless alloy body: light and strong.
- · Clean cut, without breaching or throw-away and without fatigue.
- · The use of exchangeable knife blocks and pusher sets allows thicknesses of 8, 10 or 12 mm to be achieved.
- · Controls and nuts and bolts in stainless steel.
- $\cdot$  The pusher ejects the chips and leaves the grid free.
- · Extended handle which provides optimal results with minimal effort.
- · Comfortable use: The springs at the rear leave the grid completely free.
- · The springs are highly flexible compensators which help to raise the presserejector.
- Equipped with suction feet to provide stability on the work surface.
- · Easy to clean.
- · Blade units of various sizes and holding bowls for cut potatoes are available as optional accessories.

DEFAULT EQUIPMENT

1 Knife block + pusher set of 8x8 mm.

OPTIONAL EQUIPMENT

- Knife block + pusher sets of different sizes. Recipient for cut potato. (See gastronorm containers, maximum 1/1 150mm.)

AENOR





SAMMIC, S.L. Basarte, 1 · 20720 AZKOITIA www.sammic.com

NSF/ANSI Standard 169

Reg. N° 1935/2004 CE, Reg. N° 2023/2006 CE, 2001/95 CE UNE-EN 601:2005

