



DYNAMIC PREPARATION

COMMERCIAL MEAT GRINDERS



Meat mincer PS-22R 230/50/1	SPECIFICATIONS SHEET
	Production /hour (max): 250 Kg
	– Plate diameter: Ø 82 mm
HOURLY OUTPUT: UP TO 250 KG.	Refrigerated mincer: y
 Refrigerated stainless steel countertop meat mincer for medium production levels. Complete with stainless steel cutting unit, knife and Ø 4.5 mesh plate. The highest hygiene in processing in respect of the HACCP methodology in order to improve the service to the customer. A sturdy, reliable machine, ideal for food stores and catering. Casing and feed pan in AISI 304 stainless steel. AISI 304 stainless steel external head, easy to clean. Ventilated motor, forward running and stop with low-voltage (24 V) N.V.R. Machine in conformity with " hygiene and safety regulations and specific product standards. Refrigeration Low-noise sealed compressor. Electronic thermostat for precision temperature control. Ecological refrigerating gas. 	Electrical supply: 230 V / 50 Hz / 1 ~ Plug: EU Total loading: 1100 W External dimensions (WxDxH) ·Width: 310 mm ·Depth: 438 mm ·Height: 508 mm Net weight: 40 Kg
DEFAULT EQUIPMENT Enterprise cutting unit in stainless steel. Mesh plate of 4.5 mm. OPTIONAL EQUIPMENT · Unger cutting unit (double cut): Ø 82 mm, 3 items made of stainless steel. · Mesh plates of various sizes: 3 / 4.5 / 6 / 8 mm.	
AENOR Registrada ER4437/196 SAMMIC, S.L. Basarle, 1 · 20720 AZKOITIA www.sammic.com 88/37 CEE, 2004/108/EC, 2006/95/EC, 89/109 CEE	