



DYNAMIC PREPARATION

COMMERCIAL MEAT GRINDERS



		SPECIFICATIONS SHEET
Meat mincer PS-32R 230-400/50/3		Production /hour (max): 450 Kg
		- Plate diameter: Ø 98 mm
HOURLY OUTPUT: UP TO 450 KG.		Refrigerated mincer: y
 Refrigerated stainless steel countertop meat mincer for medium production levels. Complete with stainless steel cutting unit, knife and Ø 4.5 mesh plate. The highest hygiene in processing in respect of the HACCP methodology in order to improve the service to the customer. A sturdy, reliable machine, ideal for food stores and catering. Casing and feed pan in AISI 304 stainless steel. AISI 304 stainless steel external head, easy to clean. Ventilated motor, forward running and stop with low-voltage (24 V) N.V.R. Machine in conformity with " hygiene and safety regulations and specific product standards. Refrigeration Low-noise sealed compressor. Electronic thermostat for precision temperature control. Ecological refrigerating gas. 		Electrical supply: 230 V - 400 V / 50 Hz / 3 ~ Plug: EU Total loading: 2200 W External dimensions (WxDxH) ·Width: 325 mm ·Depth: 544 mm ·Height: 553 mm Net weight: 74 Kg
DEFAULT EQUIPMENT Enterprise cutting unit in stainless steel. Mesh plate of 4.5mm.	OPTIONAL EQUIPMENT · Unger cutting unit (double cut): Ø 98 mm, 3 items made of stainless steel. · Mesh plates of various sizes: 3 / 4.5 / 6 / 8 mm.	
AENOR Registrad ER-0437/198 CMMMIC, S.L. Basarce, 1 · 20720 AZKOITIA www.sammic.com		