



Potato peeler PI-10 230/50/1

10 KG. / 22 POUNDS LOAD PER CYCLE.

**Stainless steel construction commercial potato peeler.
Also suitable to peel carrots and other similar products.
0-6 min. timer.
Removable plate for easy cleaning.**

- Construction in stainless steel.
- Lateral stirrers covered with silicon carbide abrasive (approved by NSF).
- Aluminium base plate lined with silicon carbide abrasive (approved by NSF), easily removable for cleaning purposes.
- Auto-drag of waste to the drain.
- Energy efficiency owing to engine optimisation.
- Lifiable transparent polycarbonate cover, complete with locking and safety device.
- Aluminium door with hermetic seal and safety device.
- Waterproof control board (IP65): Improved reliability against moisture and water splash.
- Water inlet system with non-return air break.
- Auxiliary contact for external electric valve.
- 0-6min timer and possibility of continuous operation.

TECHNICAL SPECIFICATIONS

Hourly production: 200 Kg / 240 Kg
Capacity per load: 10 Kg
Timer (min-max): 0' - 6'
Total loading : 550 W

Electric power supply (V) : 230 V / 50 Hz / 1 ~ / (3.5 A)
Plug: -

External dimensions (WxDxH)

- Width: 433 mm
- Depth: 635 mm
- Height: 625 mm

External dimensions with stand

- Width with stand: 433 mm
- Depth with stand: 638 mm
- Height with stand: 1040 mm

Net weight: 36,2 Kg

DEFAULT EQUIPMENT

- OPTIONAL EQUIPMENT
- Stainless steel floor stand.
 - Filter with no-foam feature.



ER-0437/196 UNE-EN ISO 9001
SAMMIC, S.L.
Basarte, 1 · 20720 AZKOITIA
www.sammic.com