



Potato peeler PI-20 230/50/1

20 KG. / 44 POUNDS LOAD PER CYCLE.

**Stainless steel construction commercial potato peeler.
Also suitable to peel carrots and other similar products.
0-6 min. timer.
Removable plate for easy cleaning.**

High capacity and production owing to lateral stirrers covered with silicon carbide abrasive (approved by NSF). Aluminium base plate lined with silicon carbide abrasive (approved by NSF). Construction in stainless steel.

- Auto-drag of waste to the drain.
- Energy efficiency owing to engine optimisation.
- Lifiable transparent polycarbonate cover, complete with locking and safety device.
- Aluminium door with hermetic seal and safety device.
- Waterproof control board (IP65): Improved reliability against moisture and water splash.
- Water inlet system with non-return air break.
- Auxiliary contact for external electric valve.
- 0-6min timer and possibility of continuous operation.

TECHNICAL SPECIFICATIONS

Hourly production: 400 Kg / 480 Kg
Capacity per load: 20 Kg
Timer (min-max): 0' - 6'
Total loading: 550 W

Electric power supply (V) : 230 V / 50 Hz / 1 ~ / (3.5 A)
Plug: -

External dimensions (WxDxH)

- Width: 433 mm
- Depth: 635 mm
- Height: 735 mm

External dimensions with stand

- Width with stand: 433 mm
- Depth with stand: 638 mm
- Height with stand: 1155 mm

Net weight: 35,8 Kg

Noise level (1m.): 70 dB(A)
Background noise: 32 dB(A)

Water Intake: 80 mm

DEFAULT EQUIPMENT

OPTIONAL EQUIPMENT

- Stainless steel floor stand.
- Filter with no-foam feature.

AENOR



Empresa Registrada



ER-0437/196 UNE-EN ISO 9001



SAMMIC, S.L.
Basarte, 1 · 20720 AZKOITIA
www.sammic.com