



Black Low-Height Bottle Coolers

SP1HC-LOW-BK / SP2HC-LOW-BH/BS / SP3HC-LOW-BH/BS

2 Years Parts & Labour Warranty

2-3 Working Days Delivery

UK Service Support



Introducing the Sterling Pro Green low-height black bottle cooler range, ideal for compact commercial spaces like pubs, restaurants, and cafés. Crafted for tight quarters, this range features embossed aluminium interiors and eco-friendly R600a refrigerants. With LED lighting, adjustable shelves, fitted locks, and timed defrost, these bottle coolers ensure efficient performance without sacrificing space.

Model	Doors	Door Type	Bottle Capacity	Nett Capacity	Temperature Range	Energy Consumption	Dimensions (mm)		
SP1HC-LOW-BK	1	Hinged	106 x 330ml	116 ltrs	+2°C to +12°C	1.27 kWh/24h	W600	D500	H840
SP2HC-LOW-BH	2	Hinged	180 x 330ml	187 ltrs	+2°C to +12°C	1.12 kWh/24h	W900	D500	H840
SP2HC-LOW-BS	2	Sliding	180 x 330ml	177 ltrs	+2°C to +12°C	1.2 kWh/24h	W900	D500	H840
SP3HC-LOW-BH	3	Hinged	274 x 330ml	280 ltrs	+2°C to +12°C	1.21 kWh/24h	W1335	D500	H840
SP3HC-LOW-BS	3	Sliding	274 x 330ml	280 ltrs	+2°C to +12°C	1.37 kWh/24h	W1335	D500	H840



Black Low-Height Bottle Coolers

SP1HC-LOW-BK / SP2HC-LOW-BH/BS / SP3HC-LOW-BH/BS



Range Specifications					
	SP1HC-LOW-BK	SP2HC-LOW-BH	SP2HC-LOW-BS	SP3HC-LOW-BH	SP3HC-LOW-BS
GTIN Code	5060750322277	5060750322284	5060750322307	5060750322291	5060750322314
Dimensions (WxDxH)	600 x 500 x 840mm	900 x 500 x 840mm	900 x 500 x 840mm	1335 x 500 x 840mm	1335 x 500 x 840mm
Doors	1	2	2	3	3
Door Type	Hinged	Hinged	Sliding	Hinged	Sliding
Bottle Capacity	106 x 330ml	180 x 330ml	180 x 330ml	274 x 330ml	274 x 330ml
Nett Capacity	116 Litres	187 Litres	177 Litres	280 Litres	280 Litres
Shelving Included	2	4	4	6	6
Exterior Finish	Black	Black	Black	Black	Black
Interior Finish	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
Temperature Range	+2°C to +12°C	+2°C to +12°C	+2°C to +12°C	+2°C to +12°C	+2°C to +12°C
Max Ambient	+32°C	+32°C	+32°C	+32°C	+32°C
Refrigerant	R600a	R600a	R600a	R600a	R600a
Energy Rating	D	C	D	C	D
Climate Class	4	4	4	4	4
Daily Energy Usage	1.27 kWh/24h	1.12 kWh/24h	1.2 kWh/24h	1.21 kWh/24h	1.37 kWh/24h
Annual Energy Usage	465 kWh/year	409 kWh/year	439 kWh/year	441 kWh/year	500 kWh/year
Power Supply	13 amp plug	13 amp plug	13 amp plug	13 amp plug	13 amp plug
Voltage	230V/50HZ	230V/50HZ	230V/50HZ	230V/50HZ	230V/50HZ
Cooling System	Fan assisted	Fan assisted	Fan assisted	Fan assisted	Fan assisted
Defrost Type	Timed	Timed	Timed	Timed	Timed
Compressor Mounting	Bottom	Bottom	Bottom	Bottom	Bottom
Multi Zone	No	No	No	No	No
Digital Display	Yes	Yes	Yes	Yes	Yes
Self Closing Doors	Yes	Yes	Yes	Yes	Yes
Reversible Doors	No	No	No	No	No
Lighting	LED	LED	LED	LED	LED
Lockable	Yes	Yes	Yes	Yes	Yes
Castors	No	No	No	No	No