Stainless Steel Upright Fridges & Freezers

SPR400S / SPF400S / SPR600S / SPF600S

2 Years Parts & Labour Warranty | 2-3 Working Days Delivery | UK Service Support

The Sterling Pro Cobus Stainless Steel upright fridge and freezer range will keep all fresh vegetables, dairy and frozen items at the perfect temperature in the busiest kitchens. The powerful fan-assisted system is powered by a super-efficient hydrocarbon refrigerant, this will keep your running costs to an absolute minimum. The food-safe ABS interior is very easy to keep hygienically clean. The door gaskets are easy to replace when required.

Model	Type	Gross Capacity	Temperature Range	Reversible Doors	Energy Rating	Dimensions (mm)		
SPR400S	Fridge	360 ltrs	0°C to +10°C	Yes	**B**	W600	D610	H1850
SPF400S	Freezer	360 ltrs	-10°C to -22°C	Yes	**B**	W600	D610	H1850
SPR600S	Fridge	580 ltrs	0°C to +10°C	Yes	**C**	W775	D730	H1850
SPF600S	Freezer	580 ltrs	-10°C to -22°C	Yes	**B**	W775	D730	H1850

Stainless Steel Upright Fridges & Freezers

SPR400S / SPF400S / SPR600S / SPF600S

Range Specifications

	SPR400S Fridge	SPF400S Freezer	SPR600S Fridge	SPF600S Freezer
GTIN Code	5060750321911	5060750321928	5060750321935	5060750321942
External Dimensions	W600 x D610 x H1850mm	W600 x D610 x H1850mm	W775 x D730 x H1850mm	W775 x D730 x H1850mm
Internal Dimensions	W455 x D445 x H1685mm	W455 x D475 x H1625mm	W635 x D545 x H1685mm	W635 x D575 x H1625mm
Packed Dimensions	W625 x D645 x H2100mm	W625 x D645 x H2100mm	W810 x D765 x H2100mm	W810 x D765 x H2100mm
Gross Capacity	360 Litres	360 Litres	580 Litres	580 Litres
Shelves Supplied	4	6	4	6
Exterior Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Interior Finish	White ABS	White ABS	White ABS	White ABS
Temperature Range	0°C to +10°C	-10°C to -22°C	0°C to +10°C	-10°C to -22°C
Max Ambient	32°C	32°C	32°C	32°C
Refrigerant	R600a	R290	R290	R290
Insulation Thickness	50mm	50mm	50mm	50mm
Nett Weight	78kg	79kg	99kg	103kg
Energy Rating	B	B	C	B
Climate Class	4	4	4	4
Power Supply	13 amp plug	13 amp plug	13 amp plug	13 amp plug
Voltage	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ
Cooling System	Static cooling with fan	Static cooling with fan	Static cooling with fan	Static cooling with fan
Defrost Type	Automatic	Manual	Automatic	Manual
Reversible Doors	Yes (no kit required)	Yes (no kit required)	Yes (no kit required)	Yes (no kit required)
Lighting	No	No	No	No
Lockable	Yes	Yes	Yes	Yes
Castors	No	No	No	No
Frost Free	No	No	No	No