

SYNERGY ST1300 PRODUCT SPECIFICATIONS



Now with SMART control technology.

- NEW Digital display
- NEW Touch control buttons
- NEW 1 - 10 power rating
- NEW Control boards - Ease of programming for engineers
- NEW Pactrol software - Allowing for a stronger signal for flame detection
- Stainless steel construction
- Comes with Garnish Rail and Slow Cook Shelf as standard
- LPG or Natural Gas - fully convertible on site
- Three variable heat settings
- Fat is atomised so no need for fat tray
- Easy clean
- Accessories available: Resting Shelf, Griddle Plate, Mobile Table, Rotisserie, Wok Cooker and Divider

DESCRIPTION	INFORMATION
Power Supply	230v / 50Hz < 1kW via 13 amp socket
Electrical Power Cord	1.5m with 3 pin plug at rear
Gas	Natural or Propane Gas (inc Butane) - convertible at site
Energy Consumption	Normal use = 17.1kW Fast Heat Up for LPG and Natural Gas 21kW
Gas Connection	3/4" BSP
Burners	Three independent burners, with simple on/off switches SMART control technology with fast heat up system
External Dimensions	WxDxH 1304 x 835 x 590mm (with slow cook shelf and garnish rail)
Surface Cooking Area	1200 x 754mm (9048cm ²)